



EXOLINE LTD Office 5, The Round House, Dormans Park Road
East Grinstead, England, RH19 2EN
Company Number: 07853326:
Tel: HU +36304233558 | UK +447874736428
E-mail: info@exoline.co.uk
Web: www.exoline.co.uk



EXOLINE® OIL STOP 10 L

Oil Adsorbent

Chemical-free oil-binding hydrophobic powder! Excellent suitable oil derivatives, oil contaminants for the removal and neutralisation of contaminants from solid pavements and from the surface!



TECHNICAL DATA SHEET

Product name: Exoline® Oil Stop Chemical-free oil-binding Hydrophobic powder! Excellent for the removal and neutralisation of oil spills from petroleum derivatives (petroleum, motor oil, gas oil, gasoline, vegetable oils and other petroleum products) from both solid surfaces and water surfaces.

General features:

- Material: natural material
- Colour: White
- Physical state: powder
- Due to its alkaline chemistry, it can cause rusting of aluminium surfaces!

Can be used for: petroleum, gas oil, petrol, kerosene, machine oils, hydraulic oils, edible oils, various organic diluents or mixtures of these.

Areas of use:

- On- and Offshore drilling of gas and oil wells, and treatment of drilling mud
- Preventing the release of products into groundwater at oil refineries and petrol stations, neutralising contamination, cleaning oil tanks
- Treatment of ballast water from tankers, neutralisation of oil and derivatives discharged into port waters during overfilling
- Neutralisation of oil pollution from ships (inside or outside the ship)
- Disaster response in the event of an oil tanker disaster
- Cleaning groundwater in mines, controlling methane intrusion (methane, oily water is flammable and explosive)
- Neutralisation of oil spills and leaks in factories, car washes, harbour oil spills
- Its high pH (8-12) makes it suitable for neutralising acidic surface waters.

Instructions for use: After removing the top cover (roof), the contents of the storage device should be sprayed onto the oil slick from a height of about 50-60 cm. Allow the applied powder to react with the oil on the oil slick for about 10 minutes. After the oil has been absorbed, simply collect the used material.

Recommended dosage: 1 litre of oil requires approximately 1 kg of additive.

Storage: no extreme storage conditions

Not for use with: strong oxidants such as organic peroxides, hydrogen peroxides (30%), and concentrated sulphur, perchloric and nitric acids.

Packaging: 10 liter plastic bucket

Place of origin: EU

Shelf life: 36 months in unopened original packaging.

Manufacturer's warranty: 10 years if properly mixed and used

Safety requirements: when working with our products, the most important safety, physical, toxicological and ecological data can be found in the product safety data sheet. The regulations on hazardous substances must be observed.

Label elements: labelling as required by (EC) No 1272/2008
Components determining the hazards: calcium hydroxide

Pictograms indicating danger: GHS07  GHS05 

Warning H instructions:

H315 – Chilling effect.

H318 – May cause serious eye damage.

Warning P instructions:

P102 – Keep out of the reach of children.

P261 – Avoid inhalation of dust, smoke, gas, mist, vapours, spray.

P262 – Do not get in eyes, on skin or clothing.

P270 – Do not eat, drink or smoke while using the product.

P280 – Use of gloves, protective clothing, eye protection, face protection is mandatory.

P305 + P351 + P338 – In case of contact, rinse gently with water for several minutes. If appropriate, remove contact lenses, if easy to do. Continue rinsing.

P305 + P310 – Contact a toxicology centre or doctor immediately.

P302 + P352 – If on skin, wash off with plenty of soapy water.

Name(s) and address(es) of the Authorised Representative(s) in Hungary: (Contractor and Contractor)

- Company: Nterworld Kft.
Address: Hungary 5800 Mezőkovácsháza, Árpád utca. 247sz.
Tel: +36304233558
E-mail: nterworldkft@gmail.com
Web: www.nterworldkft.hu
Tax number: 14641930-2-04
- Company: Baumidex Kft.
Address: 8400 Ajka, Industrial Park, North Sector 3/1
Tel: +36309270430
E-mail: pek.attila@baumidex.hu
Web: www.baumidex.hu
Tax number: 11963468-2-19

The current version of the technical fiche is available at **www.exoline.co.uk**

Person signing on behalf of and for the manufacturer:

Ferenc Sári
Director



Exoline LTD, United Kingdom
2023.01.04.