

EXOLINE® AQUA STOP B+ SMALL

Vapour- and water-tight render admixture



DECLARATION OF PERFORMANCE

Document ID: DOP-EXO-ASB-010-450ML

1. MANUFACTURER AND AUTHORISED REPRESENTATIVE IN THE EU

MANUFACTURER:

Exoline Ltd.
Office 5, The Round House
Dormans Park Road, East Grinstead
RH19 2EN, United Kingdom
E-mail: exoline@exoline.co.uk
Web: www.exoline.co.uk

AUTHORISED REPRESENTATIVE IN THE EU:

Baumidex Kft.
8400 Ajka
Industrial Park, Northern Sector 3/1
Hungary
E-mail: info@baumidex.com
Web: www.baumidex.com

2. UNIQUE IDENTIFICATION CODE OF THE PRODUCT-TYPE

Trade name	Exoline® Aqua Stop B+ Small
EAN	5060421890050

3. INTENDED USE

Exoline® Aqua Stop B+ Small: Nanotechnology-produced, hydraulically setting, universal hydrophobic admixture for the preparation of interior and exterior vapour- and water-tight renders.

Typical fields of application:

- Refurbishment of damp masonry
- Rendering of underground car parks and tunnels
- Rendering of pools and water tanks
- Protection against capillary moisture
- Masonry exposed to water and splash moisture

Render produced with or modified by the admixture:

- Provides vapour- and water-tight properties
- Has improved vapour permeability
- Provides increased durability and resistance to moisture
- Reduces water ingress and capillary water absorption

4. STANDARD APPLIED

MSZ EN 998-1:2016 - Specification for mortar for masonry / Part 1: Rendering and plastering mortar

5. AVCP SYSTEM

System of assessment and verification of constancy of performance of the construction product: **System 4**

6. DECLARED PERFORMANCE

Essential characteristic	Performance	Harmonised technical specification
Reaction to fire	A1	EN 13501-1
Capillary water absorption	$\leq 0.2 \text{ kg}/(\text{m}^2 \cdot \text{min}^{0.5})$	EN 1015-18
Vapour diffusion resistance factor	$\mu > 10$	EN 1015
Air content	$\approx 10 \%$	EN 1015
Compressive strength	$\geq 6.5 \text{ MPa}$	EN 1015-11
Flexural strength	$\geq 2.0 \text{ MPa}$	EN 1015
Bond strength	$\geq 0.5 \text{ MPa}$	EN 1015-12
Freeze-thaw resistance	XF3	EN 13687

The declared performances refer to renders produced using the admixture.

7. DECLARATION AND LIABILITY

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

The latest version is available at www.exoline.co.uk.

EXOLINE LTD

Office 5, The Round House, Dormans Park Road,
East Grinstead, England, RH19 2EN

+44 79 040 28 064

www.exoline.co.uk

exoline@exoline.co.uk

DATE OF ISSUE:

2026-02-11

SIGNATURE:

Sári Ferenc
Founder & CEO, Exoline Ltd.